Material Safety Data Sheet

Used to comply with OSHA's Hazard
Communication Standard, 29 CFR 1910.1200

SECTION I - NAME AND PRODUCT

Company Name: Flexovit Abrasives

Address: 1305 Eden-Evans Road


Angola, NY 14006

Phone: 800-689-3539

Date Updated: 5/1/2009

Product: Nonwoven Surface Conditioning

Discs & Belts



NFPA HAZARD RATING CODE

SECT	ION II -	COMP	POSIT	ΓΙΟΝ
•	- ·			- 5 \

The state of the s		OLOTTON II			<u> </u>		
	% By	OSHA	•	OSHA	ACGIH	Other	Carcin-
Ingredient	Weight	Regulate	Cas #	PEL	TLV	Limits	ogen
Corundum (Al.ox.) or silicon	25 - 30	N/A	N/A	N/A	N/A	N/A	No
carbide applied on support				· · · · · · · · · · · · · · · · · · ·			
Polymerized phenolic resin	up to 20	N/A	N/A	N/A	N/A	N/A	No
6.6 Nylon or Polyamide fibers	15 - 30	N/A	N/A	N/A	N/A	N/A	No

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

hysical State	Solid	Boiling Point		N/A	Specific Gravity (H2O=1)	N/A
apor Pressure (mm HG)	N/A	Freezing Point		N/A	Odor Threshold	N/A
/apor Density (Air=1)	N/A	Melting Point	Unknown		рН	N/A
Solubility in Water	N/A	% Volatile		N/A	Evaporation Rate	N/A
Odor/Appearance		Odorless	Coefficient of	f Water/C	Oil Distribution	N/A

SECTION IV - FIRE AND EXPLOSION DATA

the second secon				
Means Of Extinction	Carbonic anydride, dry chemical, foam	Lower And Upper Explosion Limits	· · · · · · · · · · · · · · · · · · ·	N/A
Flammable Limits	N/A	Special Fire Fighting Procedures	Wear a complete protection outfit	
Flash Point	N/A	Unusual Fire or Explosion Hazards		N/A

SECTION V - REACTIVITY DATA

Stable and inert under the normal conditions of use.

Hazardous decomposition products: Excessive heat can provoke the release of formaldehyde.

SECTION VI - HEALTH HAZARD DATA

Nonwoven abrasives are inert products, which do not cause risks when correctly stored or handled. During use, in case they are fixed on machine tools, special care has to be taken to protect the users. During use most abrasive dust particles come from the abrasive material which is being converted & from the cooling liquid, if any. Special attention has to be given particularly to the features of the abrasive material & cooling agent providing, where necessary, the right protections & exhausters.

		· · · · · · · · · · · · · · · · · · ·
Route(s) of Entry	Signs and Symptoms of Exposure	Emergency & First-Aid Procedures
Eyes	Irritation, reddening, cornea arbasion and watering.	Flush eyes with plenty of water.
	Eye inflammation	Consult a physician.
Skin	Irritation, itches, erythem	Wash with soap and water.
Inhalation	Irritation of respiratory system.	Remove to fresh air.
	Nose ache, throat ache, cough.	If symptoms persist, consult a physician.
Ingestion	N/A	No first-aid necessary.

SECTION VII- STORAGE HANDLING AND USE PROCEDURES

o not expose to inflammable sources, do not smoke.

SECTION VIII- CONTROL MEASURES

Protection Requirements and Referrals

FLEXOVIT USA, INC

Respiratory	Use antidust mask	
Ventilation	Local exhaust: If necessary	
rotective Gloves	Wear protective gloves	
Eye Protection	Wear security goggles	
Hearing Protection	Use headsets or equivalents	
Hygienic Practices	N/A	
Other	Wear reliable protective clothing	• · · · · · · · · · · · · · · · · · · ·
	COMPANY USE	er en anno de l'accessor de la company d La company de la

The information and recommendations set forth herein are taken from sources and references believed to be accurate & complete as of the date hereof. However, Flexovit USA, Inc. makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.