



## Material Safety Data Sheet

Copyright, 2011, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M™ General Purpose Adhesive Cleaner PN 08987  
**MANUFACTURER:** 3M  
**DIVISION:** Automotive Aftermarket  
  
**ADDRESS:** 3M Center  
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 03/01/11  
**Supersedes Date:** 08/10/09

**Document Group:** 07-3563-9

**Product Use:**  
**Intended Use:** Specialty Adhesive Remover (Automotive)  
**Specific Use:** Automotive Adhesive Remover

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)	64742-49-0	30 - 60
XYLENE	1330-20-7	30 - 60
PROPANE	74-98-6	10 - 30
ETHYLBENZENE	100-41-4	7 - 13
TOLUENE	108-88-3	<= 0.76455
BENZENE	71-43-2	<= 0.042475

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Aerosol

**Odor, Color, Grade:** Clear spray with solvent odor

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Extremely flammable liquid and vapor. Aerosol container contains flammable material under pressure. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel

long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Contains a chemical or chemicals which can cause cancer.

### 3.2 POTENTIAL HEALTH EFFECTS

#### Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

May be absorbed following inhalation and cause target organ effects.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

May be absorbed following ingestion and cause target organ effects.

#### Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
BENZENE	71-43-2	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
BENZENE	71-43-2	Known human carcinogen	National Toxicology Program Carcinogens
BENZENE	71-43-2	Cancer hazard	OSHA Carcinogens
ETHYLBENZENE	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**SECTION 4: FIRST AID MEASURES**

**4.1 FIRST AID PROCEDURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. Get immediate medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

**4.2 NOTE TO PHYSICIANS**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**SECTION 5: FIRE FIGHTING MEASURES**

**5.1 FLAMMABLE PROPERTIES**

Autoignition temperature	<i>No Data Available</i>
Flash Point	-42 °F [ <i>Details: (Propellant)</i> ]
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>

**5.2 EXTINGUISHING MEDIA**

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

**5.3 PROTECTION OF FIRE FIGHTERS**

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Extremely flammable liquid and vapor. Aerosol container contains flammable material under pressure. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available.

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel.

### 6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Do not pierce or burn container, even after use. No smoking while handling this material. Do not spray near flames or sources of ignition. Avoid breathing of vapors, mists or spray. Aerosol container contains flammable gas under pressure. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid contact with oxidizing agents.

### 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Do not store containers on their sides. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust ventilation on open containers. If exhaust ventilation is not available, use appropriate respiratory protection. Do not use in a confined area or areas with little or no air movement. Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields  
Indirect Vented Goggles

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Fluoroelastomer  
Polymer laminate

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters  
Half facepiece or fullface pressure demand self-contained breathing apparatus

Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
BENZENE	ACGIH	TWA	0.5 ppm	Skin Notation*
BENZENE	ACGIH	STEL	2.5 ppm	Skin Notation*
BENZENE	OSHA	TWA	1 ppm	29 CFR 1910.1028
BENZENE	OSHA	STEL	5 ppm	29 CFR 1910.1028
BENZENE	OSHA	TWA	10 ppm	
BENZENE	OSHA	CEIL	25 ppm	
ETHYLBENZENE	ACGIH	TWA	100 ppm	
ETHYLBENZENE	ACGIH	STEL	125 ppm	
ETHYLBENZENE	CMRG	TWA	25 ppm	
ETHYLBENZENE	CMRG	STEL	75 ppm	
ETHYLBENZENE	OSHA	TWA	435 mg/m3	
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)	CMRG	TWA	50 ppm	
PROPANE	OSHA	TWA	1800 mg/m3	
TOLUENE	ACGIH	TWA	20 ppm	
TOLUENE	CMRG	STEL	75 ppm	Skin Notation*
TOLUENE	OSHA	TWA	200 ppm	
TOLUENE	OSHA	CEIL	300 ppm	
XYLENE	ACGIH	TWA	100 ppm	
XYLENE	ACGIH	STEL	150 ppm	
XYLENE	CMRG	TWA	50 ppm	

XYLENE	CMRG	STEL	75 ppm
XYLENE	OSHA	TWA	435 mg/m3

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists  
 CMRG: Chemical Manufacturer Recommended Guideline  
 OSHA: Occupational Safety and Health Administration  
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Specific Physical Form:</b>	Aerosol
<b>Odor, Color, Grade:</b>	Clear spray with solvent odor
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	-42 °F [ <i>Details: (Propellant)</i> ]
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Density</b>	0.738 g/ml
<b>Vapor Density</b>	>=1 [ <i>Ref Std: AIR=1</i> ]
<b>Vapor Pressure</b>	50 psi [ <i>Details: CONDITIONS: @ 70F</i> ]
<b>Specific Gravity</b>	0.738 [ <i>Ref Std: WATER=1</i> ]
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Solubility in Water</b>	Nil
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Hazardous Air Pollutants</b>	92.6 % weight [ <i>Test Method: Calculated</i> ]
<b>Volatile Organic Compounds</b>	738 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
<b>Volatile Organic Compounds</b>	100.0 % weight [ <i>Test Method: calculated per CARB title 2</i> ]
<b>Kow - Oct/Water partition coef</b>	<i>No Data Available</i>
<b>Percent volatile</b>	100 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	738 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
<b>Viscosity</b>	<i>No Data Available</i>

**SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat  
 Sparks and/or flames

10.2 Materials to avoid

Strong oxidizing agents

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

Facility must be capable of handling aerosol cans. Dispose of empty product containers in a sanitary landfill.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable), D018 (Benzene)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number(s):**

60-4550-3068-8, 60-4550-4585-0, 60-9800-2679-7

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ETHYLBENZENE	100-41-4	7 - 13
XYLENE	1330-20-7	30 - 60

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
XYLENE (Benzene, 1,4-dimethyl-)	1330-20-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

### STATE REGULATIONS

Contact 3M for more information.

### CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
BENZENE	71-43-2	*Male reproductive toxin
BENZENE	71-43-2	**Carcinogen
BENZENE	71-43-2	*Developmental Toxin
ETHYLBENZENE	100-41-4	**Carcinogen
TOLUENE	108-88-3	*Female reproductive toxin
TOLUENE	108-88-3	*Developmental Toxin

\* WARNING: contains a chemical or chemicals which can cause birth defects or other reproductive harm.

\*\* WARNING: contains a chemical which can cause cancer.

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact 3M for more information.



## INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

Health: 2 Flammability: 4 Reactivity: 0 Special Hazards: None  
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

Health: 2 Flammability: 4 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

### Revision Changes:

Copyright was modified.

Section 3: Potential effects from eye contact was modified.

Section 3: Potential effects from inhalation information was modified.

Section 8: Eye/face protection information was modified.

Section 8: Skin protection - recommended gloves information was modified.

Section 8: Respiratory protection - recommended respirators information was modified.

Section 14: Transportation legal text was modified.

Section 3: Other health effects information was modified.

Section 15: Inventories information was modified.

Section 9: Density information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 2: Ingredient table was modified.

Section 15: EPCRA 313 information was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 3: Carcinogenicity table was modified.

Section 15: California proposition 65 ingredient information was modified.

Section 15: TSCA section 12[b] text was added.

Section 15: TSCA section 12[b] information was added.  
Section 6: 6.2. Environmental precautions heading was added.  
Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.  
Section 10.1 Conditions to avoid heading was added.  
Section 10.2 Materials to avoid heading was added.  
Section 6: Personal precautions information was added.  
Section 6: Environmental procedures information was added.  
Section 6: Methods for cleaning up information was added.  
Section 10: Materials to avoid physical property was added.  
Section 10: Conditions to avoid physical property was added.  
Section 6: Clean-up methods heading was added.  
Section 6: Release measures information was deleted.  
Section 6: Release measures heading was deleted.  
Section 10: Materials and conditions to avoid physical property was deleted.  
Section 8: Exposure guidelines legend was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**