

DATE OF PREPARATION March 24, 1986

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyer's risk. We make no guarantee that the health and safety precautions we have suggested will be adequate for all individuals and/or situations involving its handling and use. No warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet.

### Section I

MANUFACTURER'S NAME Activa Products, Inc.

STREET ADDRESS 288 Littleton Rd. CITY, STATE, AND ZIP CODE Westford, MA 01886  
Gateway #24

EMERGENCY TELEPHONE NO. (508) 692-9300

PRODUCT CLASS Adhesive

MANUFACTURER'S CODE IDENTIFICATION

TRADE NAME

DOT PROPER SHIPPING NAME Not a regulated material.

### Section II - HAZARDOUS INGREDIENTS

| INGREDIENT/CAS NUMBER   | PERCENTAGE RANGE | OSHA PEL | ACGIH TLV | LEL | VAPOR PRESSURE mm Hg, 20°C |
|---|------------------|----------|-----------|-----|----------------------------|
| This product does not contain regulated levels of hazardous ingredients as defined in 29 CFR 1910.1200. |                  |          |           |     |                            |

NA - NOT APPLICABLE

### Section III - PHYSICAL DATA

NE - NOT ESTABLISHED

BOILING RANGE >200° F      pH 4.5      PERCENT VOLATILE BY WEIGHT 47      WEIGHT PER GALLON 9.1 lbs.

### Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT

NA

EXTINGUISHING MEDIA

Liquid material - non-flammable. Use water spray, foam, dry chemical or carbon dioxide on dried product.

USUAL FIRE AND EXPLOSION HAZARDS

There is the possibility of pressure build-up in closed containers when heated. Water spray may be used to cool the containers.