Grinding Wheel

#266

## **MATERIAL SAFETY DATA SHEET**

Used to comply with OSHA's Hazerd Communication Standard, 29 CFR 1910.1200

## SECTION I - NAME AND PRODUCT


Flexovit East U.S.A., Inc. 154 Potomac Ave., Unit A Tallmadge, Ohio 44278

Phone: (800) 321-8800 Fax: (888) 321-8800

Updated: 5/99

Product: All Type 27, 28, 29, and Type 1 wheels

including Flexon, Flexoel, and Speedoflex products.



NFPA HAZARD RATING CODE

SECTION II - COMPOSITION								
	% By	OSHA		OSHA	ACGIH	Other	Carcin-	
Ingredient	Weight	Regulate	Cas #	PEL	TLV	Limits	ogen	
Aluminum Oxide	60 - 80	No	1344-28-1	NA NA	10mg/m	N/A	No	
Silicon Carbide	NA	No	409-21-2	NA NA	NA NA	N/A	No	
Zirconium Oxide	0 - 12	No	1314-23-4	NA NA	10mg/m	N/A_	No	
Calcium Hydroxide	NA	No	N/A	NA	5mg/m	N/A	No	
Barlum Sulfate	NA	No	N/A	0.5mg/m	10mg/m	N/A	No	
Iron Sulfide	NA	No	1317-37-9	NA NA	NA	N/A	No	
Florides	NA	No	16984-48-B	2.5mg/m	2.5mg/m	N/A	No	
Phenolic Resin	0 - 15	No	9003-35-4	5 P.P.M.	5 P.P.M.	N/A	No	
Fiber Glass	0 - 5	No	N/A	15mg/m	10mg/m	N/A	No	
Aluminum or Steel	0.1 - 1	No	N/A	NA NA	NA	N/A	No	
Zino	NA	No	N/A	NA	NA	N/A	No	
							<u></u>	
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS								
Bolling Point N/A			Specific C	Specific Gravity (H20=1) 2			2 - 4	
Vapor Pressure (mm Hg.)		N/A	Melling P	Melling Point			N/A	
Vapor Density (AIR=1)	N/A Evaporation Rate (Butyl Acetate≠1) N/A			N/A				
Solubility in Water Slight			Appearan	Appearance/Odor Dark colored solid.				
May give off some odor in use.								
SECTION IV - FIRE AND EXPLOSION DATA								
Means Of Extinction Water or carbon dioxide.			Lower And	Lower And Upper Explosion Limits N/A				
Flammable Limits N/A			Special Fi	Special Fire Fighting Procedures Nor			None	
Flash Point N/A Unusual Fire or Explosion Hazards					None			

	SECTION V - REACTIVITY DATA						
Stable - Avoid excessive moisture, high relative humidity, temperature extremes and contact with acids or solvents							
Not incompatible with any materials							
Hazardous Polymerzation will not occur							
Dust and organic lumes are generated in use. Do not exceed TLV's.							
	SECTION VI - HEALTH HAZARD DATA						
Route(s) of Entry	Signs and Symptoms of Exposure	Emergency and First-Aid procedures					
×	May cause coughing and shortness of breath during	Terminate exposure and remove to					
Dust Inhalation	grinding. May affect breathing capacity.	Iresh air. Obtain medical assistance,					
Ingestion	No known adverse effects, but not recommended.	Obtain medical assistance.					
Absorption	Not absorbed through skin,	N/A					
	Grinding wheel may cause abrasions. Dust may	Terminate exposure and remove to					
Skin contact	cause skin Irritation.	fresh air. Obtain medical assistance.					
Eye	Dust or fumes may cause eye irritation.	Fresh air and medical assistance.					
Other	Excessive noise levels may exist in use.	Cease use. Obtain medical assistance.					
Medical conditions such as emphysema and asthma may be aggravated during grinding.							
	SECTION VII- STORAGE HANDLING AND USE PROCEDURES						
Handling and storage procedures - Avoid damage to wheel. Do not drop. Do not use a wheel that has been damaged or dropped. Avoid excessive temperatures in storage. Always handle in accordance with ANSI B7.1.							
Normal clean up procedures should be used if material is released.							
Dispose of waste in a sanitary landiiii in accordance with state, local and federal regulations.							
Always use in accordance with ANSI Z43.1 and OSHA 1910.215. Do not use dropped or demaged wheels. Do not							
use without machine guard in place. Do not exceed maximum RPM on wheel.							
SECTION VIII- CONTROL MEASURES							
Protection Requirements and Referrals							
Respiratory	OSHA or NIOSH approved respirator if TLV's exceeded. See OSHA 29 CFR 1910.134						
Ventilation	Local and mechanical exhaust recommended. See ANSI Z43.1. Refer to OSHA 29 CFR 1910.94.						
Protective Gloves	Not required but use if desired.						
Eye Protection	Required. Refer to OSHA 29 CFR 1910,133.						
Hearing Protection	Required. Refer to OSHA 29 CFR 1910.95.						
Other	Apron and/or face shield if desired.						
lygianic Practices Wash with scap and water after handling and grinding.							
COMPANY USE							
The information and recommendations set forth herein are taken from sources and references believed to be							

accurate and complete as of the data hereof. However, FlexOvit® U.S.A. Inc. makes no expressed or implied war-

ilability to any user thereof.

ranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no